



Archived resources

For further resources and
documentation please visit us:
www.cinos.net

CSC-1

Full-featured wireless presentation system for high-profile meeting rooms and boardrooms



ClickShare makes connecting to the meeting room's video system a matter of clicking a button. This one click wonder not only helps the presenter get the presentation on-screen in a second, but it also allows the other people in the meeting to participate more actively. Sharing can be done via laptop PC or MAC, or via iOS and Android-powered mobile devices. The result is enhanced meeting efficiency and better decision-making.

More pixels, more content

If you are driving two projectors, two screens, or Double HD canvas, the full-featured CSC-1 Base Unit is the right choice. This unit is fully compatible with the ClickShare Buttons and the apps for mobile devices, and was optimized for use in high-profile meeting rooms and boardrooms.

Optimized collaboration experience

By enabling to display the content of up to 4 users simultaneously, the CSC-1 Base Unit brings a complete Clickshare collaboration experience. 64 Buttons can be wirelessly connected to the Base Unit, ready to share. Furthermore, perfectly synchronized sound and video ensures that movie clips can be optimally enjoyed. And dynamic content from iPads and iPhones can be shown using the optional ClickShare Link.

ClickShare set

A ClickShare CSC set consists of a Tray, four Buttons and a Base Unit. Additional items are sold separately.

BARCO

Visibly yours

Product specifications

CSC-1

General specifications	
Operating system	Windows XP Pro, Vista Pro and Windows 7 Pro 32 & 64 bit, Windows 8/8.1 and 8/8.1 Pro Mac OS X 10.6, 10.7, 10.8, 10.9
Video outputs	DisplayPort, Single link DVI-I VGA (via included convertor, highest resolutions only with reduced blanking) In "Dual screen" mode, connection can occur either through DVI and DisplayPort, or through VGA and DisplayPort.
Frame rate	Up to 30 fps (from software version V1.03.00.0001 onwards)
Output resolution	DVI WUXGA (1920x1200) DisplayPort panoramic format (2560x1080) available from ClickShare Base Unit software v01.02.00.09 onwards
Input Resolutions	Up to 2048x1536 (QXGA)
Noise Level	Max. 28dBA
Number of sources simultaneous on screen	4
Number of simultaneous connections	64
Audio	Audio compatible from ClickShare Base Unit software v01.02.00.09 onwards
iPad, iPhone and Android compatibility	Available via ClickShare app for static content. For iOS devices, the optional ClickShare Link and AppleTV can be used to show dynamic content, from ClickShare Base Unit software v01.02.00.09 onwards
Authentication protocol	WPA2-PSK
Encryption	AES CCMP
Wireless transmission protocol	IEEE 802.11 a/g/n
Reach	Max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit
Band	2.4 GHz and 5 GHz
Connections	1x Ethernet LAN 4x (back) + 1x (front) USB Analog line out on mini jack socket (3.5mm) Analog line in on mini jack socket (3.5mm)
Temperature range	Operating: +5°C to +40°C (+41°F to +104°F) Storage: -20°C to +60°C (-4°F to +140°F)
Humidity	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing
Altitude	Max 3000m (9842 ft)
Lifetime	MTBF = 40,000h (90% confidence level) MTBF = 100,000h (60% confidence level) MTBF conditions: · Environment: Ground Benign · Temperature: 25°C · Method: MIL-HDBK-217F Notice 2
System requirements	PC minimum requirements: · CPU: Intel Pentium Dual Core E2140 – 2 * 1600 Mhz (or equivalent: AMD Athlon 64 X2 3800+ - 2 * 2000 Mhz) · Memory: 1024 MB RAM · OS: Windows XP Pro/Home (SP3) (Windows Vista/7 supported, but requires more RAM) PC recommended requirements: · CPU: Intel Core 2 Duo E4600 – 2 * 2400 Mhz (or equivalent: AMD Athlon 64 X2 4800+ - 2 * 2500 Mhz) · Memory: 2048 MB RAM · OS: Windows XP Pro/Home, Windows Vista, Windows 7, Windows 8 MAC · CPU: Intel Core 2 Duo · Memory: 2048 MB RAM · OS: Mac OS X 10.6, 10.7, 10.8
ClickShare Base Unit dimensions	
Dimensions (HxWxD)	181mm (incl. antennas) x 260mm x 276mm (Min.) / 7.125" (incl. antennas) x 10.236" x 10.9" (Min.)
Weight	2.6 kg/5.75 lb

Generated on: 05 May 2014
Technical specifications are subject to change without prior notice.
Please check www.barco.com for the latest information.

BARCO

Visibly yours

For further resources and
documentation please visit us:
www.cinos.net