



# Archived resources

For further resources and  
documentation please visit us:  
**[www.cinos.net](http://www.cinos.net)**

# Enzo<sup>®</sup>

NMX-MM-1000 (FG3211-01)



## Overview

Enzo is a device purposely designed for the collaboration space to easily access content and documents stored on USB, on the web, or in the cloud.

## Common Applications

Ideal for any conference room Enzo is the simplest, fastest way to present and share information during a meeting or lecture.

## Features

- **"Instant-On" File and Web Browsing** – Access web content or USB thumb drive files within seconds of entering the room
- **IT Friendly** – Avoids OS updates, viruses and other PC-related maintenance hassles and costs
- **End of Session Data Purge** – Prevents unintended disclosure of confidential information
- **Native NetLinx Device** – Control Enzo using a touch panel and NetLinx controller
- **PoE, Pass-Through Ethernet and Small Form Factor** – Easy to Install practically anywhere

## Specifications

GENERAL	
Dimensions (HWD)	1 3/8" x 5 13/16" x 3 1/4" (34.80 mm x 147.32 mm x 83.41 mm)
Weight	1.1 lb (.5 Kg)
Mounting Options	<p>Surface Mount: AVB-VSTYLE-SURFACE-MNT, V Style Single Module Surface Mount Brackets, quantity 2 of 760896, included</p> <p>Rack Mount Adapter: NMX-MM-RKA, Enzo Rack Mount Adapter (FG3211-60), not included</p>

	The rack mount adapter is designed for use with V Style Rack Mounting Tray (FG1010-720/721) and V Style Rack Mounting Shelf (FG3201-60), not included
Regulatory Compliance	FCC IC CE IEC 60950-1 cULus 60950-1 VCCI C-Tick RoHS / WEEE Compliant
Included Accessories	AVB-VSTYLE-SURFACE-MNT, V Style Single Module Surface Mount Brackets, quantity 2 of 760896
Optional Accessories	<ul style="list-style-type: none"> <li>•PS-POE-AF-TC, PoE Injector, 802.3AF Compliant (FG423-83)</li> <li>•CBL-HDMI-FL, HDMI High Speed Flat Cable with RedMere® Technology (FG10-2180-16)</li> <li>•NMX-MM-RKA, Enzo Rack Mount Adapter (FG3211-60)</li> <li>•AVB-VSTYLE-RMK, V Style Rack Mounting Tray (FG1010-720/721)</li> <li>•NMX-VRK, V Style Rack Mounting Shelf (FG3201-60)</li> </ul>

ACTIVE POWER REQUIREMENTS	
Power Consumption	13 W, (Max)
Power over Ethernet	PoE, 802.3AF
Power Indicator	(1) LED (red/green), solid red at start of boot, blinking green during boot, solid green after boot is complete

POWER SUPPLY	
External, Required	NMX-MM-1000 requires the use of a 802.3AF Compliant Power over Ethernet (PoE) Injector or PoE capable Ethernet Switch, not included  Enzo is compatible with PS-POE-AF-TC (FG423-83)

ENVIRONMENTAL	
Temperature (Operating)	0° C to 40° C (32° F to 104° F)
Temperature (Storage)	-20° C to 70° C (-4° F to 158° F)
Humidity (Operating)	5% to 85%, non-condensing

CONTROL	
NetLinx	Master Code: URL, Auto, Listen ICSP Security: Yes
RS-232	(1) DB-9 Male Supported Baud Rates 150 to 115,200 Used to control display* *To be released in a future firmware release
Operation Button	Quick press: Sleep Press-and-hold: System Settings

<b>FUNCTIONAL CAPABILITIES</b>	
Management Interface	On-screen configuration
NetLinx	On-Screen Keypad: Number of buttons, 12 Number of text rows, 3  Note: Control can be disabled
Supported Documents	Office: .doc, .docx, .xls, .xlsx, .ppt, .pptx, .pdf
Supported Document Sources	Dropbox USB Drive (only one can be connected to Enzo at a time) Web Browser  Note: Document sources can be disabled
Supported Document Sharing	Email (all sources) Dropbox (Dropbox documents only)  Note: Email document sharing can be disabled
Supported Images	.png, .jpg, .bmp, .gif
Supported Videos	.mp4 with H.264 video and AAC audio
Email	SMTP with SSL or TLS encryption  Note: Email can be disabled
Maximum Number of Web Applications Supported	TBA
Supported Web Browser	Chromium-based web browser that supports HTML5. Plug-ins, including Flash, are not supported.  Note: Web browsing can be disabled
Wallpaper	Supported Formats: .png Resolutions: any, 1920 x 1080 preferred Customizable: Can select a single wallpaper applied to all Enzo pages EXCEPT for start session page

<b>MEMORY</b>	
RAM	2 GB
Flash	16 GB, (12 GB user accessible)

<b>HDMI</b>	
Output Connection	(1) HDMI Type A Female
Output Signal Type Support	HDMI
Output Resolution	720p, 1080p

<b>ANALOG AUDIO</b>	
Output Connection	(1) 3.5 mm stereo audio jack
Output Level (Max)	1 Vp-p into 10 kOhms
Output Impedance	200 Ohms

<b>ETHERNET</b>	
Connection	(2) RJ-45, Auto MDI/MDI-X
Description	10/100 BASE-T
Link/Act Indicator	(1) LED (green), on for link, blink off for activity
Speed Indicator	(1) LED (yellow), on for 100 BASE-T, off for 10 BASE-T

Note	Integrated 2 port Ethernet switch allows a connection to PoE (power and network), along with an auxiliary connection for another device to the network drop in the room
------	---

USB	
Connection	(4) USB 2.0 Type A Connect USB drive to display documents Connect keyboard and mouse
+5 V Current Output (Max)	4 W total across all USB connections
Wireless Keyboard & Mouse	Supports 2.4 GHz RF wireless keyboard and mouse using wireless dongle (not included)  Note: Does not support Bluetooth keyboard and mouse

**About AMX**

AMX hardware and software solutions simplify the implementation, maintenance, and use of technology to create effective environments. With the increasing number of technologies and operating platforms at work and home, AMX solves the complexity of managing this technology with reliable, consistent and scalable systems. Our award-winning products span control and automation, system-wide switching and audio/video signal distribution, digital signage and technology management. They are implemented worldwide in conference rooms, homes, classrooms, network operation / command centers, hotels, entertainment venues, broadcast facilities, and more. ©2014 AMX. All rights reserved.

**Specifications subject to change. Revised 10-April-2014.**

AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153

For further resources and  
documentation please visit us:  
**[www.cinos.net](http://www.cinos.net)**