

Resources

For further resources and documentation please visit us:

www.cinos.net

ClickShare C-10

Making hybrid collaboration flow in medium-sized and large meeting rooms



- Full BYOD support
- Seamless content sharing with Button or Desktop App
- Enhanced security, connected and cloud managed
- Full interactivity with touch back, blackboarding, annotation
- Delivered with 1 Button

Even in a hybrid meeting, participants can be engaged, inspired and active. ClickShare C-10 adds interactive features to full BYOD, easy wireless presentation in any medium to large meeting room. It is the wireless presentation hub that makes your hybrid meetings flow in one click.

Find out what's new in the latest ClickShare update

Full BYOD content sharing

With ClickShare C-10, you can start a meeting and get your content on screen within seconds. No matter the device you are using. Plug & Play with the ClickShare Button, that works perfectly on both Pc or Mac. Go for workflow integration with the ClickShare App on laptop, mobile or tablet. Or enable full BYOD on a 4K canvas: screen mirroring with Airplay, GoogleCast and Miracast works flawlessly.

Anyone, including guests, can share content wirelessly to the central room display with our one-click meeting experience. Two users can share side by side in full HD on screen. No cables, no software to download, no training needed.

Enjoy interactive, creative meetings

ClickShare C-10 users can benefit from advanced interactive features including local view of the room display, decide what you share (either a full screen or a single window), annotation, blackboarding and touch back support that allows users to control the touchscreen in the room. Designed especially to make your meetings richer and more dynamic. C-10 makes hybrid collaboration flow in your creative meetings, brainstorms and discussion in one click.



ClickShare C-10 Barco



Enhanced security and seamless integration

Designed for enterprise rollouts, the IT-grade C-10 offers you enhanced security features (ISO27001 certified) and a wide range of connectivity options. With the XMS Cloud Management Platform you enjoy remote management of units and clear analytics to drive your digital workplace. For practical questions on network deployment of the ClickShare Conference range, check our technical support or get in touch with your Barco contact.

Boost collaboration in your existing fixed conference room

The ClickShare C-10 can be used stand-alone or in combination with your existing conference room. It empowers hybrid meetings in existing Microsoft Teams, Zoom or Webex conference rooms with simple, one-click wireless content sharing. ClickShare completes the existing set-up and makes hybrid collaboration flow. Designed to fit your business perfectly and evolve with it. With flexibility for the future built in, it's one of the smartest investments you can make in your meeting room or conference room ecosystem.

PRODUCT SPECIFICATIONS

CLICKSHARE C-10

Operating system Wiredoors 81x10/LIT mecOS 10.13 and higher. Apply 105.12 and higher (ClickShare Buttons) LPMI ClickShare Buttons 1 ACURSHAR (ACURSHAR) Desktop 6 Mobile Native protocols Aroley, Google Cast Minecast* Acurshare (Acurshare Apply 105.12 and higher (Acurshare Apply 105.12	General specifications	
Audio output HDMI USB 1X USB-A 1X USB-C CLickShare Buttons 1 CLickShare App Desktop 6 Mobile Native protocols Airplay, Google Cest, Mirecest* With Buttons and/or Appl Noise Level Max 25dBA @ 0-30°C Maximum number of simultaneous connections (with Buttons and/or Appl) Noise Level Max 25dBA @ 0-30°C Authentication protocol WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.11 Alghr/aca and IEEE 802.11 Surging the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEEE 802.1X Using the ClickShare Button in network integration mode WPR2-PSK or IEE	Operating system	Android v9 and higher (ClickShare App)*
USB 1X USB-A, 1X USB-C ClickShare Buttons 1 ClickShare App Desktop b Mebile Native protocols Airplay, Google Cast, Miracast* Maximum number of simultaneous connections with Buttons and/or Appl 32 Mosie Level Max 25dBA @ 0-30°C Max 30dBA @ 30-40°C Authentication protocol Max 25dBA @ 0-30°C Max 30dBA @ 30-40°C Authentication protocol UFEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Adjustable with signal strength modulation, max 30m (100 ft) between ClickShare Button and ClickShare Button in network integration mode Frequency band 2.4 GHZ and 5 GHz (DES channels supported in select number of countries) Connections 32 Emental And 15cBi (123°C to 140°C 143°C to 140°C) Live Billype-C 2.0 (front); 1x USB Type A 2.0 (front) Temperature range Operating 0°C to 440°C (43°C to 14°C to 140°C) Max 35°C (95°F) at 3000m Storage -20°C to 60°C (44°C to 140°C) Mariations Recipion 10 os 85% relative humidity, non-condensing Operation 20 os 85% relative humidity, no	Video outputs	4K UHD (3840*2160) @ 30Hz. HDMI 1.4b
ClickShare Buttons 1 ClickShare App Desktop B Mobile Native protocols Arpley, Google Cost, Miracast* Maximum number of simultaneous connections (with Buttons and/or App) Moise Level Share App Max. 25d8A (g. 0-30°C Max. 35d8A g. 30 A0°C Max.	Audio output	HDMI
ClickShare App Desktop 6 Mobile Native protocols Airplay, Google Cast, Miracast* Maximum number of simultaneous connections (with Buttons and/or App) 32 Noise Level Max. 25dBA @ 0-30°C Max. 30dBA @ 30.40°C Authentication protocol WPA2-PSK in is sand alone mode WPA2-PSK in IEEE 802113. Using the ClickShare Button in network integration mode Wireless transmission protocol EEE 80211 a/g/m/ac and IEEE 80215.1 Reach Adjustable with Signal strength modulation, max. 30m (100 ft) between ClickShare Button and Clickshare Base Unit Frequency band 2.4 GHZ and 5 GHz (DTS channels supported in select number of countries) Connections 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front). Ix USB Type A 2.0 (front) Temperature range Questing in Cito 1+40°C (1-41°C t-41°C t-41°C) (4-41°C) (4-4	USB	1 X USB-A, 1 X USB-C
Native protocols Airplay, Google Cast, Miracast* Maximum number of simultaneous connections (with Buttons and/or App) \$2 Noise Level Max. 25dBA @ 0.30°C Authentication protocol WPA2-PSK in stand alone mode WPA2-PSK in Standard in Standard	ClickShare Buttons	1
Maximum number of simultaneous connections (with Buttons and/or App) 32 Noise Level Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C Authentication protocol WPA2-PSK in stand allone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration and IEEE 802.1X using the ClickShare Button in network integration and IEEE 802.1X using the ClickShare Button in network integration and IEEE 802.1X using the ClickShare Button in network integration with	ClickShare App	Desktop & Mobile
Noise Level Max 50dBA @ 0-30°C Max 30dBA @ 30-40°C Authentication protocol WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15 1 Reach Adjustable with signal strength modulation, max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz Frequency band 2.4 GHZ and 5 GHz (DPS channels supported in select number of countries) Connections 1. Ethernet LAN I GBit 1x USB Type-C 2.0 (front), 1x USB Type A 2.0 (front) Humidity Operating O°C to +40°C (+32°F to +104°F) Max 35°C (95°F) at 35000m Storage. 20°C to +60°C (-4°F to +104°F) Max 35°C (95°F) at 35000m Storage. 20°C to +60°C (-4°F to +104°F) Anti-theft system Kensington lock Certifications FCC/CE Touch screen support 6 Interactivity Yes Room Dock (peripheral support) No Local view Yes Network connection 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Op	Native protocols	Airplay, Google Cast, Miracast*
Authentication protocol Max 30dBA (a 30-40°C) Authentication protocol WPA2_PSK in stand alone mode WPA2_PSK or IEEE 802_1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802_11 a/g/n/ac and IEEE 802_15_1 Reach Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) Connections 1x Ethernet LAN 1Gbit 1x USB Type A 2.0 (front) x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front) Temperature range 2 Coperating 0°C to +40°C (+32°F to +104°F) Max 37C (95°F) at 3000m Storage 20°C to +40°C (+32°F to +104°F) Munidity 3 Storage 20°C to +60°C (+47°F to +140°F) Humidity 8 Scrage 20°C to +60°C (+47°F to +140°F) Anti-theft system 8 Kensington lock Certifications FCC/CE Touch screen support 8 Interactivity Yes No Local view Yes Network connection An 6 WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare Ves <tr< th=""><th></th><th>32</th></tr<>		32
WFA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode Wireless transmission protocol IEEE 802.11 a/g/n/ac and IEEE 802.15.1 Reach Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Buston and ClickShare Base Unit in Frequency band 2.4 GHZ and 5 GHz Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) Connections 1x Ethernet LAN 1Gbit 1x USB Type A 2.0 (front) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max. 35°C (95°P) at 3000m Storage: -20°C to +60°C (-42°F to +140°F) Humidity Storage: -00 you've leavity humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock Certifications FCC/CE Touch screen support 6 Interactivity Yes Room Dock (peripheral support) No Local view Yes Network connection LAN 8 WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug	Noise Level	· · · · · · · · · · · · · · · · · · ·
Reach Adjustable with signal strength modulation, max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz. Frequency band 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) Connections 1x Ethernet LAN 1 Gbit 1x USB Type A 2.0 (front). x USB Type-C 2.0 (front): 1x USB Type A 2.0 (front) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-44°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock Certifications FCC/CE Touch screen support 6 Interactivity Yes Room Dock (peripheral support) No Local view Yes Network connection LAN 8 WiFi Management and reporting Yes Warranty 1 year standard, 5 years coverage via SmartCare * * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Authentication protocol	
Frequency band 2.4 GHZ and 5 GHz Frequency band 2.4 GHZ and 5 GHz Frequency band 2.4 GHZ and 5 GHz Connections	Wireless transmission protocol	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Connections 1x Ethernet LAN 1Gbit 1x USB Type A 2.0 (front) Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: 20°C to +60°C (+4°F to +140°F) Humidity Storage: 20°C to +60°C (+4°F to +140°F) Humidity Storage: 20°C to +60°C (+4°F to +140°F) Anti-theft system Kensington lock Certifications FCC/CE Touch screen support 8 Interactivity Yes Room Dock (peripheral support) No Local view Yes Network connection LAN 8 WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions 34 mm x 135 mm x 135 mm Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Reach	ClickShare Base Unit
Temperature range Operating: 0°C to +40°C (+32°F to +104°F) Max: 55°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Anti-theft system Kensington lock Certifications FCC/CE Touch screen support & Interactivity Yes Room Dock (peripheral support) No Local view Yes Network connection LAN & WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Standard 110/220 V AC plug Power supply Standard 110/220 V AC plug Power consumption Operational, 5-10W, 24W Max	Frequency band	2.4 GHZ and 5 GHz (DFS channels supported in select number of countries)
Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) Humidity Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relati	Connections	
Anti-theft system Kensington lock Certifications FCC/CE Touch screen support & Interactivity Room Dock (peripheral support) No Local view Yes Network connection LAN & WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates CtickShare Base Unit dimensions Power supply Power consumption Operational: 5-10W, 24W Max	Temperature range	Max: 35°C (95°F) at 3000m
Certifications FCC/CE Touch screen support & Interactivity Yes Room Dock (peripheral support) No Local view Yes Network connection LAN & WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Humidity	
Touch screen support & Interactivity Room Dock (peripheral support) No Local view Yes Network connection LAN & WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Anti-theft system	Kensington lock
Room Dock (peripheral support) Local view Yes Network connection LAN & WiFi Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Certifications	FCC/CE
Local viewYesNetwork connectionLAN 6 WiFiManagement and reportingYesWarranty1 year standard. 5 years coverage via SmartCare* depends on configuration, available in future firmware updatesClickShare Base Unit dimensions* depends on configuration available in future firmware updatesDimensions (HxWxD)34 mm x 135 mm x 135 mmPower supplyStandard 110/220 V AC plugPower consumptionOperational: 5-10W, 24W Max	Touch screen support & Interactivity	Yes
Network connectionLAN & WiFiManagement and reportingYesWarranty1 year standard. 5 years coverage via SmartCare** depends on configuration, available in future firmware updatesClickShare Base Unit dimensions34 mm x 135 mm x 135 mmPower supplyStandard 110/220 V AC plugPower consumptionOperational: 5-10W, 24W Max	Room Dock (peripheral support)	No
Management and reporting Yes Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Local view	Yes
Warranty 1 year standard. 5 years coverage via SmartCare * depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Network connection	LAN & WiFi
* depends on configuration, available in future firmware updates ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Management and reporting	Yes
ClickShare Base Unit dimensions Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	Warranty	1 year standard. 5 years coverage via SmartCare
Dimensions (HxWxD) 34 mm x 135 mm x 135 mm Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	*	* depends on configuration, available in future firmware updates
Power supply Standard 110/220 V AC plug Power consumption Operational: 5-10W, 24W Max	ClickShare Base Unit dimensions	
Power consumption Operational: 5-10W, 24W Max	Dimensions (HxWxD)	34 mm x 135 mm x 135 mm
	Power supply	Standard 110/220 V AC plug
Weight 900 gr	Power consumption	Operational: 5-10W, 24W Max
	Weight	900 gr

Last updated: 16 Dec 2021

 $Technical\ specifications\ are\ subject\ to\ change\ without\ prior\ notice.\ Please\ check\ www.barco.com\ for\ the\ latest\ information.$



For further resources and documentation please visit us:

www.cinos.net