



Archived resources

For further resources and
documentation please visit us:
www.cinos.net

PHXG-91B

8,500 ANSI lumens, XGA, single-chip DLP projector



This 8,500 ANSI lumens projector with XGA resolution is perfectly suited for large-screen professional projection in your stylish meeting room and boardroom.

What you'll love about this projector

- **Stylish design** that seamlessly blends in with your office interior
- **High-quality images** with an unmatched level of detail and contrast
- **Button-free and cable-free** for simple operation and less clutter
- **Reliable DLP technology** for true ease of mind
- **Easily upgradable** with future connectivity add-ons
- **Low cost of ownership** thanks to DLP technology and sealed optics
- Preset image modes that allow for **flexible color management**
- **Intuitive control menu** with the most common features at your fingertips
- **User-friendly remote control** that features just one button

ClickShare Inside

Supporting the integration of optional connectivity modules, the Barco Corporate AV projectors are fully future-proof and can easily be upgraded with extra functionalities. Based on Barco's wireless presentation system ClickShare, the '**ClickShare Inside**' option can be nicely integrated under the hood of the projector and allows users to wirelessly share their content on-screen, for true collaboration.

BARCO

Visibly yours

Product specifications**PHXG-91B**

| | |
|---|---|
| Projector type | XGA single-chip DLP projector |
| Technology | 0.70" DMD |
| Color wheel | 4S standard (RGBW) |
| Resolution | 1,024 x 768 XGA |
| Brightness | 8,500 ANSI lumens / 6,200 ANSI lumens (eco-mode) (complies with ISO 21118) |
| Contrast ratio | 2,800:1 |
| Brightness uniformity | 70% |
| Aspect Ratio | 4:3 |
| ScenergiX | Yes |
| Lens type | H lens |
| Lenses | 1.7-2.3:1; 0.8-1.0:1; 1.3-1.8:1; 2.2-2.9:1; 2.9-4.7:1; 4.7-9.0:1 |
| Optical lens shift | Vertical: -0% to +118% / horizontal: -20% to +20% |
| Color correction | Yes |
| Lamps | 2 x 350W AC lamp |
| Lamp lifetime | Up to 2,000 hours (full power) / Up to 4,000 hours (eco mode) |
| Sealed DLP™ core | Yes |
| Optical dowsers | Yes |
| Advance Picture in Picture | PIP |
| Orientation | table - ceiling |
| WARP | Yes |
| Integrated web server | Yes |
| Keystone correction | Yes |
| Inputs | 5 BNC (RGBHV, component), S-VIDEO, D-SUB 15-pin, HDMI, DVI-D (HDCP) |
| Input Resolutions | up to WUXGA (1,920 x 1,200) 60Hz |
| Software tools | Projector Toolset |
| Control | IR, RS232, RJ45 |
| Network connection | 10/100 base-T, RJ-45 connection |
| Power requirements | 100-240V / 50-60Hz |
| Max. power consumption | 910W / 690W(eco mode) / 0.3W (standby) |
| Noise level (typical at 25°C/77°F) | 44 dBA (bright mode) / 39 dBA (eco mode) |
| Operational ambient temperature | 5-40°C / 41°-104°F |
| Operational humidity | 30-90% |
| Dimensions (WxLxH) | 510 x 660 x 263 mm |
| Weight | 21kg |
| Shipping dimensions (WxLxH) | 650 x 840 x 415 mm |
| Shipping Weight from Factory | 26.5 kg |
| Certifications | CB test certificate, US emc, US safety, CE emc and safety, CCC emc and safety |
| Warranty | 3 years standard warranty (contact your local sales rep for details per region) |

For further resources and
documentation please visit us:
www.cinos.net