



Archived resources

For further resources and
documentation please visit us:
www.cinos.net

UN I Video Wall Displays

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level ¹	Orientation ²	Input
UN462A 2,3	46 / 117	700	P	L, P, FU	HDMI In/Out, DP In/Out, DVI-D, VGA
UN462VA 2,3	46 / 117	500	P	L, P, FU	
UN492S 1,3	49 / 123	700	P	L, P, FU	
UN492VS 1,3	49 / 123	500	P	L, P, FU	
X554UNS-2 2	55 / 140	700	P	L, P, FU	HDMI, DP In/Out, DVI-D, VGA
X554UNV-2 2	55 / 140	500	P	L, P, FU	
X555UNS 1	55 / 140	700	P	L, P, FU	
X555UNV 1	55 / 140	500	P	L, P, FU	
UN551S 1	55 / 140	700	P	L, P, FU	
UN551VS 1	55 / 140	500	P	L, P, FU	

Panel Technology IPS¹ or PVA²



- Enhanced imaging performance via the SpectraView™ engine
- Easy set-up with Auto TileMatrix
- Secure reliability and longevity



NEC Display Wall Calibrator

The aim of the NEC Display Wall Calibrator software is to automatically adjust multiple displays used in a video wall so that the colour characteristics closely match, thereby creating the visual illusion of a single large display.

NaViSet Administrator 2



Unified remote management software for NEC desktop monitors, large format displays and projectors.

SpectraView Engine



Advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.

Open Modular Intelligence (OMI)

Future ready expansion to upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute module 3 or signal interfaces for content feed and computing.

Protective & Mirror Glass

Guaranteed reliability even under the toughest conditions is achieved with robust protective glass designed to withstanding external impacts.

Available for NEC MultiSync C / V / P / UN Series.

NEC MultiSync P Series displays can be transformed into highly attractive and engaging devices with semi-transparent mirror glass.

Multi-Touch

Based on the latest touch technologies, NEC offers a wide range of multi-touch solutions for various applications. Multi-touch solutions are available throughout all NEC MultiSync LFD Series, including video walls.

Coloured Bezel

Colour match NEC MultiSync V and P Series displays to suit their environment with coloured bezels in any colour of the RAL range.

NEC Service Plus

We take the guessing out of the set-up and maintenance. Our customers can concentrate on their business activities, confident that their IT infrastructure is underwritten by the Service Plus promise:

- 5 years warranty extension
- Ad-hoc warranty extension
- De- / re-install service

Document Name: Large Format Displays Pocket Guide
 Document Revision: Edition 4, 2019
 Document Date: 03/19
 Created by: fg

For more information visit us at www.nec-display-solutions.com



NEC Display Solutions

Large Format Displays

Orchestrating a brighter world **NEC**

E Series | Entry Level Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
E327	32 / 81	350	S	L	3 HDMI, VGA
E437Q ¹	43 / 109	350	S	L	3 HDMI, VGA
E507Q ¹	50 / 127	350	S	L	3 HDMI, VGA
E557Q ¹	55 / 140	350	S	L	3 HDMI, VGA
E657Q ¹	65 / 165	350	S	L	3 HDMI, VGA



- Slim design and integrated speakers
- Future-ready connectivity
- Standalone operation



C Series | Value Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
C431	43 / 109	400	P	L, P, FU	3 HDMI, DP, VGA
C501	50 / 127	400	P	L, P, FU	3 HDMI, DP, VGA
C551	55 / 140	400	P	L, P, FU	3 HDMI, DP, VGA
C651Q ¹	65 / 165	350	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
C751Q ¹	75 / 189	350	P	L, P	3 HDMI, DP: 2 In, 1 Out
C861Q ¹	86 / 217	350	P	L, P	3 HDMI, DP: 2 In, 1 Out
C981Q ¹	98 / 248	350	P	L, P	3 HDMI, DP: 2 In, 1 Out



- Integrated Media Player
- Slim profile and modern design for seamless integration
- Low reflective panel and “pixel-free” viewing experience for excellent readability¹



V Series | Value Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
V323-2	32 / 81	450	S	L, P	HDMI, DP, DVI-D In/Out, VGA
V404 ²	40 / 102	500	P	L, P, FU, FD	2 HDMI, DP: 2 In, 1 Out, DVI-D, VGA
V484 ²	48 / 122	500	P	L, P, FU, FD	
V554 ²	55 / 140	500	P	L, P, FU, FD	3 HDMI, DP: 2 In, 1 Out
V554Q ^{1,2}	55 / 140	500	P	L, P	
V654Q ^{1,2}	65 / 165	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
V754Q ^{1,2}	75 / 189	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
V864Q ^{1,2}	86 / 217	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
V984Q ^{1,2}	98 / 248	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out



- Open Modular Intelligence for scalable computing power
- Reliable colour reproduction
- “Pixel-free” viewing experience¹



P Series | Professional Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
P404	40 / 102	700	P	L, P, FU, FD	2 HDMI, DP: 2 In, 1 Out, DVI-D, VGA
P484	48 / 122	700	P	L, P, FU, FD	
P554	55 / 140	700	P	L, P, FU, FD	
P654Q ¹	65 / 165	700	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
P754Q ¹	75 / 189	650	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out



- Open Modular Intelligence for scalable computing power
- Superb readability in bright light environments
- Long-term operation in demanding environments



XHB Series | High Brightness

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Haze Level*	Orientation**	Input
X554HB	55 / 140	2700	S	L, P	HDMI, DP In/Out, DVI-D, VGA
X754HB	75 / 191	2500	S	L, P	



- Programmable Ambient Light Sensor
- Sunlight-proof operation
- Automated thermal management



NEC InfinityBoards | Collaboration Solutions

MultiSync® Model	Size inch/cm	Brightness in cd/m ²	Touch Technology	Orientation**	USB Hubs
55" InfinityBoard	55 / 140	500	InGlass™	L, P, FU	4x USB 3
65" InfinityBoard 2.0	65 / 165	500	InGlass™	L, P, FU	4x USB 3
75" InfinityBoard 2.0	75 / 191	500	InGlass™	L, P, FU	4x USB 3
86" InfinityBoard 2.0	86 / 217	500	InGlass™	L, P, FU	4x USB 3



- Create, collaborate, communicate
- Natural writing experience
- Simplified video conferencing



For further resources and
documentation please visit us:
www.cinos.net