

Archived resources

For further resources and documentation please visit us:

www.cinos.net

PRO PLUS HDBASET 8X8 MODULAR MATRIX

MX-0808-PP-POH-CUSTOM with Power-over-HDBaseT™ and Routed Serial Control



KEY FEATURES

- · Custom built to meet the exact specifications for any application or requirement
- Modular design achieves diverse and near endless configuration options (3x8, 4x8, 6x8, 8x12, 6x14, 12x16, 10x32) up to 16x112 specification.
- One matrix mixes both digital & analogue video sources and audio devices
- · Matrix configuration specifications completed and submitted via new Web Widget

The WyreStorm Modular MX-0808-PP-POH-CUSTOM Pro Plus Matrix takes truly custom AV distribution to the next level with a totally modular, built-to-order HDBaseT matrix solutions.

The MX-0808-PP-POH-CUSTOM features a completely modular design, RS-232 routing capabilities, integrated Power over HDBaseT (POH) and near-limitless selection of input configurations to offer residential and commercial electronic system integrators with most flexible, scalable, fully featured HDBT matrix to date. Integrators can select from a range of digital and analogue transmission cards that can used interchangeably and tailor the matrix configuration to the exact specifications of each system and application.

ADDITIONAL FEATURES & BENEFITS

- 70m/230ft uncompressed transmission of 36bit 1080p video, HD audio & 2-Way IR over a single Cat5e/6.
- Available in an 8x8 and 16x16 model (end Q1 2014).
- New QuickSync technology improves switching time between sources.
- Power over HDBaseT technology powers the receivers from the matrix device.
- Routes discrete RS232 commands to any output via the built-in serial port.
- 3D compatible frame packing (Blu-Ray) and stereoscopic (satellite and cable).
- Assembled and delivered within 10 business days (UK and US)
- Integrated cable testing via link LED's on transmission card and receiver.

- TX-POH-010 card features a duplicate HDMI port mirrors the HDBaseT output for connecting AVR's, fiber and coax extender sets.
- TX-POH-020 source loop card enables matrix cascading option, supporting up to 392 displays
- TX-POH-030 card allows easy connection of Sonos or Airport Express devices to the WyreStorm AMP, allowing multi-room audio streaming from single devices using existing infrastructure and WyreStorm's AMP-001-010.
- Seamless integration with leading control systems via RS232 and LAN, including WyreStorm Enado.

IN THE BOX

1 x MX-0808-PP-POH-CUSTOM Matrix

1 x Remote control

1 x Mounting brackets (pair)

1 x Manual

8 x IR emitters 1 x USB serial cable 8 x IR Receivers



SPECIFICATIONS Dimensions (WxHxD): 440mm × 100mm x 340mm /17.3" x 3.9 x 13.4" Weight: 6.7Kg / 14.8lb **Operating Temperature Range:** 0 to +35°C (32 to +95°F) **Operating Humidity Range:** 5 to 90 % RH (no condensation) Video Amplifier Bandwidth: 6.75Gbps Input Video Signal: 0.5-1.0 volts p-p Input DDC Signal: 5 volts p-p (TTL) Maximum Single Link Range: 1080p 36bit Deep Colour Min: 5m/16.4ft - Max: 60m/197ft (Cat5e/6), 70m/230ft with **Transmission Distance:** (Cat6a/7) using WyreStorm RX-1UTP-IR-70-POH display receiver or AMP-001-010 digital amplifier (Under perfect transmission conditions including straight cable runs with no electrical interference, bends, kinks, patch panels or wall outlets.) Video Format Supported: VESA: 640x480, 800x600,1024x768, 1280x1024, 1600x1200, 1920x1200, 1920x1080 DTV/HDTV: 480i/576i/480p/576p/720p/1080i/1080p **Output Video:** HDMI v1.4 with full 3D compatibility with Frame packing/ (Blu-ray) and Stereoscopic (satellite/ cable broadcasts) Audio Format Supported: HDBaseT: DTS Master HD, Dolby True HD, PCM 5.1, 7.1, stereo Power Supply: 100-240V AC **Power Consumption:** 170 Watts (Max.) British Thermal Unit (BTU): 580.1 Rack Space Required: 2U

TRANSMISSION CARD FEATURES:

- TX-POH-010 70m/230ft HDBaseT output with mirrored HDMI output, HDMI input, IR input
- TX-POH-020 70m/230ft HDBaseT output with HDMI passthru for connection to additional cascaded matrix units, HDMI input, IR input
- TX-POH-030 70m/230ft HDBaseT output with mirrored digital and analogue audio output, HDMI input, IR
- TX-POH-040 70m/230ft HDBaseT output with analogue audio input, HDMI output, IR input
- TX-POH-050 70m/230ft HDBaseT output with DVI onput, IR onput
- TX-POH-060 70m/230ft HDBaseT output only, IR input
- TX-POH-070 70m/230ft HDBaseT output with VGA / stereo audio input, IR input
- TX-POH-080 HDMI input only

TRANSMISSION CARDS





TX-POH-010

TX-POH-020





TX-POH-030

TX-POH-040





TX-POH-050

TX-POH-o6o





TX-POH-070

TX-POH-o8o

To custom configure a WyreStorm Modular Matrix and submit it online, visit the Web tool at www.wyrestorm.com or place a Modular Matrix order by contacting your authorized WyreStorm sales representative or distribution partner.











Follow us on Twitter



Watch us on Youtube WvreStormHD

WyreStorm Technologies




LinkedIn WyreStorm Technologies

HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance

SMALL RESIDENTIAL FULL HD DISTRIBUTION WITH HI FI AUDIO DISTRIBUTION OVER 1 CAT5E/6

KEY SYSTEM FEATURES

- Easier installation with only one Cat5e/6 cable to each display and zone.
- Deliver fully uncompressed 1080p video switching, HiFi audio and end user control to each zone.
- Centralized A/V sources with local audio devices, including AMP-010-001 and personal devices.
- · Recreate this Total WyreStorm Distribution & Control Solution for small or large residential applications.





For further resources and documentation please visit us:

www.cinos.net